

# SwitchProbes

---

This chapter provides information on the SwitchProbe network monitoring probes. The information is organized into the following sections:

- Product Overview
- Standard Features
- Product Numbers

---

**Note** Documentation for SwitchProbes is available in two forms: on a CD-ROM called Cisco Connection Documentation, Enterprise Series and printed books. A CD and hard-copy installation documentation ship with each chassis, and a configuration note ships with each component ordered. All configuration notes are available on the CD. Additional CDs and a subscription CD update service are also available.

You can also access Cisco technical documentation on the World Wide Web URL <http://www.cisco.com>. For more information, see the chapter “Documentation” at the end of the catalog.

---

## Product Overview

Cisco now offers a complete family of standalone enhanced remote monitoring (RMON) probes for monitoring any segment, ring, or switch link in an enterprise network. Cisco SwitchProbes employ the powerful RMON and RMON2 standards-based agent technology. SwitchProbes also provide value-added extensions for ISL VLAN monitoring, NetFlow-to-RMON2 proxy (optional), and RMON proxy for monitoring of Catalyst 1700, 1900, 2100, and 2800 series desktop switches. A typical enterprise network can be equipped with multiple SwitchProbes with one probe connected to each critical link or to a switch’s diagnostic port. SwitchProbes are managed and controlled from a centrally located network management console.

Fast Ethernet, FDDI, and CDDI SwitchProbes use a high performance Pentium processor to monitor all RMON and RMON2 groups. The high performance Pentium processor allows users to gather RMON-based statistics for all network traffic activity.



## Standard Features

SwitchProbe network monitoring probes support the following features:

- High-performance Pentium processor in Fast Ethernet, CDDI, and FDDI SwitchProbes; high-performance 486 processor in Ethernet and Token Ring SwitchProbes
- Support for all nine Ethernet RMON groups and ten Token Ring RMON groups as defined in RFCs 1757 and 1513
- RMON2 for 7-layer concurrent monitoring of multiple network parameters
- Support for monitoring of half- and full-duplex Fast Ethernet links
- In-band/out-of-band configuration support via BOOTP and TFTP
- Support for duplicate Internet Protocol (IP) address detection
- Support for 62.5/125-micron multimode FDDI
- SMT support for FDDI/CDDI for enterprise-wide standard diagnostics
- Support for single- and dual-attached FDDI physical connections
- Compatible with any SNMP -based network management system

SwitchProbes can be easily installed by simply typing in the IP address and connecting the probe to the network. Once connected, SwitchProbes immediately begin collecting RMON statistics. Upon power on, the SwitchProbe automatically collects default statistics for etherStats, host, history, and matrix groups. The SLIP interface can be used to dial in or out from a remote probe.

SwitchProbes can be easily managed from a remote site through in-band or out-of-band links. BOOTP support allows any probe to be automatically assigned an IP address and name. TFTP allows any probe to be updated with the most current release of software. NSLogin allows the administrator to change the probe's configuration files from a central site.

Table 290 and Table 291 list product specifications, and Table 292 lists product numbers for SwitchProbe network monitoring probes.

The SwitchProbe for FDDI has built-in support for monitoring and capturing station management (SMT) frames. This capability allows TrafficDirector to filter and decode all SMT frames and to present an active ring map and topology for all FDDI devices on an FDDI segment.

**Table 290 Ethernet and Token Ring SwitchProbe Specifications**

Description	Specifications
Dimensions (H x W x D)	3 x 12 x 13.5" (7.6 x 30.5 x 34.3 cm)
Weight	11 lbs (5 kgs)
Ethernet interfaces	AUI (Thicknet) RJ-45 (10BaseT) BNC (Thinnet)

Description	Specifications
Token Ring interfaces	9-pin D type STP RJ-45 socket UTP
Memory	4-MB standard for Ethernet and Token Ring models 8-MB standard for dual Ethernet and dual Token Ring models
Temperature	32 to 131°F (0 to 55°C)
Humidity	5% to 95% noncondensing
Power	120 VAC/240 VAC, 50/60 cycles 60W autoswitching
Agency approvals	UL, CSA, FCC, TUV, CE, VCCI, AUSTEL

**Table 291 Fast Ethernet, CDDI, and FDDI SwitchProbe Specifications**

Description	Specifications
Dimensions (H x W x D)	6.75 x 17 x 16" (17.1 x 43.2 x 40.6 cm)
Weight	24 lbs (10.9 kgs)
CDDI interfaces	RJ-45 accepts Category 5 UTP or Category 5 sheath-shielded, 100-ohm twisted pair cable with TP-MIC plug
FDDI interfaces	Single or dual SC type connectors accept SC-to-SC or SC-to-MIC multimode fiber-optic cable Console, SLIP: 9-pin D male supporting EIA/TIA-232 <sup>1</sup> signals (SLIP support is standard)
Fast Ethernet interfaces	Half-duplex TX, 100BaseTX, RJ-45 Full-duplex TX, 100BaseTX, RJ-45 Half-duplex FX, 100BaseFX, SC connector Full-duplex FX, 100BaseFX, SC connector
Side-band Ethernet	AUI (Thicknet), BNC (Thinnet), RJ-45(10BaseT) selected through internal strapping
Side-band Token Ring	9-pin D type (STP), RJ-45 UTP autoselected
Memory	8 MB standard for Fast Ethernet models 8 MB standard for CDDI models 16 MB standard for FDDI models
Temperature	32 to 104°F (0 to 40° C)
Humidity	5% to 95% noncondensing
Power	120 VAC/230 VAC, 50/60 cycles 200W
Agency approvals	UL, CSA, FCC, TUV, CE, VCCI, AUSTEL

1. EIA/TIA-232 was known as recommended standard RS-232 before its acceptance as standard by the Electronic Industries Association (EIA) and Telecommunications Industry Association (TIA).

## Product Numbers

Table 292 lists product numbers for the SwitchProbes. For Workgroup SMARTnet product numbers, refer to Table 357 in the chapter “Service and Support.” For documentation product numbers, refer to Table 374 in the chapter “Documentation.”

**Table 292 SwitchProbe Product Numbers**

<b>Description</b>	<b>Memory</b>	<b>Product Number</b>
Ethernet SwitchProbe, monitors 1 segment	4 MB	WS-PROBE-ETH-4M
Dual Ethernet SwitchProbe, monitors 2 segments	8 MB	WS-PROBE-DUAL-ET
Token Ring SwitchProbe, monitors 1 ring	4 MB	WS-PROBE-TR-4M
Dual Token Ring SwitchProbe, monitors 2 rings	8 MB	WS-PROBE-DUAL-TR
CDDI SwitchProbe with Ethernet side band	8 MB	WS-PROBE-SCDDI-ET
CDDI SwitchProbe with Token Ring side band	8 MB	WS-PROBE-SCDDI-TR
FDDI (SAS) SwitchProbe with Ethernet side band	16 MB	WS-PROBE-SFDDI-ET
FDDI (SAS) SwitchProbe with Token Ring side band	16 MB	WS-PROBE-SFDDI-TR
FDDI (DAS) SwitchProbe with Ethernet side band	16 MB	WS-PROBE-DFDDI-ET
FDDI (DAS) SwitchProbe with Token Ring side band	16 MB	WS-PROBE-DFDDI-TR
Fast Ethernet, half duplex, TX	8 MB	WS-PROBE-FE-HD-TX
Fast Ethernet, full duplex, TX	8 MB	WS-PROBE-FE-FD-TX
Fast Ethernet, half duplex, FX	8 MB	WS-PROBE-FE-HD-FX
Fast Ethernet, full duplex, FX	8 MB	WS-PROBE-FE-FD-FX