

# Regulatory Compliance

---

This appendix contains information for customers installing systems in the United Kingdom and Europe. Refer to this section about your location.

## Information for United Kingdom Use Only

### Warnings

Interconnection directly, or by way of other apparatus, of ports marked:

“Safety Warning—See instructions for use”

with ports marked or not so marked may produce hazardous conditions on the network and that advice should be obtained from a competent engineer before such a connection is made.

The ports marked 10BaseT, Console and PCMCIA have a safety warning applied to them as follows:

“These ports do not provide isolation sufficient to satisfy the requirement of BS6301; apparatus connected to these ports should either have been approved to BS6301 or have previously been evaluated against British Telecommunications plc (Post Office) Technical Guides 2 or 25 and given permission to attach; any that other usage will invalidate any approval given to this apparatus.”:

This apparatus must be connected to a mains socket outlet with a protective earth contact.

Connection of Power Supply. The Cisco 1020 is intended for use when supplied with power from a supply provided 200 to 240VAC, 50/60 Hz up to 1 Amp.

#### **Information for European Community Use Only**

---

Other usage will invalidate any approval given to this apparatus if as a result it ceases to comply with BS6301: 1989.

### **Information for European Community Use Only**

The ports marked “10BaseT”, “Console,” and “PCMCIA” are SELV circuits. SELV circuits should only be connected to other SELV circuits.